



Application

Lazio-Oil 0W-40 is a premium synthetic lubricant engineered for the optimal performance of petrol and diesel-powered cars, as well as light commercial vehicles. It is formulated to meet the maintenance intervals recommended by manufacturers, ensuring superior protection and efficiency for your engine.

This high-performance oil guarantees excellent cold starts and provides exceptional lubrication to all engine components, even in extreme low-temperature conditions. Its carefully selected raw materials work synergistically to preserve engine performance by reducing wear and preventing the formation of harmful deposits.

With its outstanding viscosity properties, Lazio-Oil 0W-40 ensures superior lubrication across all driving conditions. It minimizes friction, leading to reduced fuel consumption and lower CO2 emissions, contributing to both enhanced engine longevity and environmental sustainability.

Specifications

ACEA A3/B3, A3/B4 | **API SN** • BMW LL-04 • Ford WSS-M2C937-A • MB 226.5
• Renault RN 0700, 0710 • MB-Approval 229.5 • Porsche A40 • VW 502 00, 505 00

Characteristics

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m ³	846
Viscosity at 100°C	ASTM D 445	mm ² /s	13.1
Viscosity Index	ASTM D 2270	-	181
Viscosity at -35°C	ASTM D 5293	mPa·s	6000
Flash point COC	ASTM D 92	°C	228
Pour point	ASTM D 5950	°C	-54