



## Application

Lazio-Oil 5W-30 is a synthetic technology engine oil with "mid SAPS" characteristics, specially formulated for the latest generation of gasoline and diesel cars, as well as commercial vehicles, requiring a lubricant that meets ACEA C3 specifications.

This high-performance oil excels in its exceptional detergent and dispersant properties, effectively preventing the buildup of deposits within the engine. It is particularly effective in combating carbon deposit formation in high-temperature areas, such as the piston zones. Careful selection of high-quality raw materials ensures optimal wear protection for engine components, extending their lifespan.

Designed for excellent low-temperature start-up performance, Lazio-Oil 5W-30 also contributes to fuel efficiency, reducing both fuel consumption and CO2 emissions.

## Specifications

**ACEA C3** • MB 229.51, 226.51 • Renault RN0720

## Characteristics

Properties	Method	Unit	Typical
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	850
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	12
Viscosity Index	ASTM D 2270	-	163
Viscosity at -30°C	ASTM D 5293	mPa·s	5800
Flash point COC	ASTM D 92	°C	224
Pour point	ASTM D 97	°C	-36
T. B. N.	ASTM D 2896	mg KOH/g	6.3